

DOZERS DQD

Tractafric equipment



D07FRS

D8R

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

YEAR

2014

HOURS

9788

LOCATION

Cameroun

VIN

9EM09279

AVAILABILITY

Sold





DOZERS

D8R

Technical specifications

ENGINE

ENGINE MODEL

NET POWER	242 kW
NET POWER, ISO 9249/SAE J1349	242 kW
NET POWER: ISO 9249 (DIN)	328 mhp
EMISSIONS	Complies with Brazil MAR-1 emissions standard and China Stage III r
VERSION NUMBER	19B
BIODIESEL COMPATIBILITY	Up to B100*

Engine power at 1,900 rpm. The announced net power is the availab

*Cat engines are compatible with the following renewable/alternation

C15 Cat

WEIGHT

NOTE (1)

NOTE (2)

OPERATING WEIGHT 38,834 kg

MAINTENANCE CAPACITIES

FUEL TANK 600 I

STANDARD SU

OPERATING WEIGHT 38,834 kg

GROUND PRESSURE 88.2 kPa





DOZERS

D8R

Technical specifications

STANDARD SHOE WIDTH 610 mm

BLADE Semi-U Blade

BLADE CAPACITY 10.3 m³

LGP

OPERATING WEIGHT 37,525 kg

GROUND PRESSURE 52.3 kPa

STANDARD SHOE WIDTH 965 mm

BLADE Semi-U Blade

BLADE CAPACITY 9.9 m³

DESERT/HEAVY ABRASION

OPERATING WEIGHT 39,153 kg

GROUND PRESSURE 88.2 kPa

STANDARD SHOE WIDTH 610 mm

BLADE Semi-U Blade

BLADE CAPACITY 10.3 m³

WASTE HANDLER TRACK LOADER

OPERATING WEIGHT 38,621 kg





DOZERS

D8R

Technical specifications

GROUND PRESSURE 88.2 kPa STANDARD SHOE WIDTH 610 mm BLADE

Semi-U Sanitary Blade

BLADE CAPACITY 21.2 m³

WASTE HANDLER TRACK LOADER LGP

OPERATING WEIGHT 37,312 kg

GROUND PRESSURE 52.3 kPa

STANDARD SHOE WIDTH 965 mm

BLADE Semi-U Sanitary Blade

BLADE CAPACITY 22.2 m³



