

822D

Tractafric equipment



822D

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

YEAR

2021

HOURS

2052

LOCATION

Cameroun

VIN

S8T00584

AVAILABILITY

Sold





822D

Technical specifications

MODEL

MODEL SEM822D

MAIN SPECIFICATIONS

OPERATING WEIGHT 24,000kg

GROUND PRESSURE 71.2kPa

GROUND CLEARANCE 400mm

MAX. SLOPE 30°

ENGINE

ENGINE MODEL WD12G240E206

RATED POWER 175kW/235hp

WORKING TOOL

BLADE TYPE SU blade

BLADE CAPACITY 6.4m³

BLADE WIDTH 3,660mm

BLADE HEIGHT 1,520mm

MAX. BLADE DIGGING DEPTH 570mm

MAX.BLADE LIFT GROUND CLEARANCE 1,140mm





822D

Technical specifications

MAX.OUTPUT RIMPULL	350kN
RIPPER TYPE	Multi-Shank Ripper Single- Shank Rippe
MAX. DIGGING DEPTH OF RIPPER	860mm
MAX. CLEARANCE UNDER TIP	640mm

POWERTRAIN

ТҮРЕ	dual-path, closed loop electronically controlled hydrostatic drive sys
TRAVEL SPEED-F/R	infinitely variable speeds 0-10km/h
STEERING & BRAKE	hydrostatic steering; wet,multi-disc brake
MINIMUM STREEING RADIUS	4,215mm

UNDERCARRIAGE

TRACK SHOE WIDTH-SINGLE	560mm
TRACK SHOE QUANTITY	40
TRACK LENGTH ON GROUND	2,948mm
TRACK GAUGE	2,000mm
TRACK ROLLER QUANTITY	7
CARRIER ROLLER QUANTITY	2

HYDRAULIC SYSTEM





822D

Technical specifications

TYPE enter close, pilot contro

IMPLEMENT HYDRAULIC SYSTEM PRESSURE 19MPa

SERVICE REFIL CAPACITIES

FUEL TANK 460L

COOLING SYSTEM 45L

HYDRAULIC TANK 160L

PIVOT SHAFT CASE(EACH SIDE) 0.8L

FINAL DRIVE(EACH SIDE) 40L



