



DOZERS

D8R

Tractafric
equipment



DOZERS

D8R

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

YEAR

2016

HOURS

5446

LOCATION

Cameroun

VIN

JR800248

AVAILABILITY

Sold

D8R

ENGINE

ENGINE MODEL	C15 Cat
NET POWER	242 kW
NET POWER, ISO 9249/SAE J1349	242 kW
NET POWER: ISO 9249 (DIN)	328 mhp
EMISSIONS	Complies with Brazil MAR-1 emissions standard and China Stage III n
VERSION NUMBER	19B
BIODIESEL COMPATIBILITY	Up to B100*
NOTE (1)	Engine power at 1,900 rpm. The announced net power is the availab
NOTE (2)	*Cat engines are compatible with the following renewable/alternativ

OPERATING WEIGHT	38,834 kg
------------------	-----------

FUEL TANK	600 l
-----------	-------

OPERATING WEIGHT	38,834 kg
------------------	-----------

GROUND PRESSURE	88.2 kPa
-----------------	----------

DOZERS

D8R

Technical specifications

STANDARD SHOE WIDTH	610 mm
---------------------	--------

BLADE	Semi-U Blade
-------	--------------

BLADE CAPACITY	10.3 m ³
----------------	---------------------

LGP

OPERATING WEIGHT	37,525 kg
------------------	-----------

GROUND PRESSURE	52.3 kPa
-----------------	----------

STANDARD SHOE WIDTH	965 mm
---------------------	--------

BLADE	Semi-U Blade
-------	--------------

BLADE CAPACITY	9.9 m ³
----------------	--------------------

DESERT/HEAVY ABRASION

OPERATING WEIGHT	39,153 kg
------------------	-----------

GROUND PRESSURE	88.2 kPa
-----------------	----------

STANDARD SHOE WIDTH	610 mm
---------------------	--------

BLADE	Semi-U Blade
-------	--------------

BLADE CAPACITY	10.3 m ³
----------------	---------------------

WASTE HANDLER TRACK LOADER

OPERATING WEIGHT	38,621 kg
------------------	-----------

DOZERS

D8R

Technical specifications

GROUND PRESSURE	88.2 kPa
STANDARD SHOE WIDTH	610 mm
BLADE	Semi-U Sanitary Blade
BLADE CAPACITY	21.2 m ³

WASTE HANDLER TRACK LOADER LGP

OPERATING WEIGHT	37,312 kg
GROUND PRESSURE	52.3 kPa
STANDARD SHOE WIDTH	965 mm
BLADE	Semi-U Sanitary Blade
BLADE CAPACITY	22.2 m ³