



DOZERS

D6R2

Tractafric
equipment



DOZERS

D6R2

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

YEAR

2016

HOURS

4689

LOCATION

Cameroon

VIN

SSS00401

AVAILABILITY

Sold

DOZERS

D6R2

Technical specifications

ENGINE

ENGINE MODEL C9 Cat

POWER - NET 148 kW

NOTE (1) The announced net power is the power available at the flywheel when the engine is operating at 2300 rpm.

D6R2 (TIER 2/STAGE II)

EMISSIONS Chinese Stage II emissions standards for non-road engines, equivalent to EPA Tier 2.

STANDARD - NET RATED POWER - ISO 9249/SAE J134 141 kW

STANDARD - NET RATED POWER - ISO 9249 (DIN) 192 mhp

XL/LGP - NET RATED POWER - ISO 9249/SAE J1349 158 kW

XL/LGP - NET RATED POWER - ISO 9249 (DIN) 215 mhp

D6R2 (TIER 3/STAGE III)

EMISSIONS Chinese Stage III emissions standards for non-road engines, equivalent to EPA Tier 3.

STANDARD - NET RATED POWER - ISO 9249/SAE J134 162 kW

STANDARD - NET RATED POWER - ISO 9249 (DIN) 220 mhp

XL/LGP - NET RATED POWER - ISO 9249/SAE J1349 176 kW

XL/LGP - NET RATED POWER - ISO 9249 (DIN) 239 mhp

MAINTENANCE CAPACITIES

DOZERS

D6R2

Technical specifications

FUEL TANK	424 l
-----------	-------

WEIGHT

OPERATING WEIGHT	18,984 kg
------------------	-----------

OPERATING WEIGHT - D6R2 (S)	18,984 kg
-----------------------------	-----------

OPERATING WEIGHT - D6R2 (SU)	19,066 kg
------------------------------	-----------

OPERATING WEIGHT - D6R2 (A)	19,448 kg
-----------------------------	-----------

OPERATING WEIGHT - D6R2 XL (SU)	19,914 kg
---------------------------------	-----------

OPERATING WEIGHT - D6R2 XL (A)	19,969 kg
--------------------------------	-----------

OPERATING WEIGHT - D6R2 LGP (S)	21,661 kg
---------------------------------	-----------

STANDARD TRACK UNDERCARRIAGE

GROUND PRESSURE - BLADE A (ISO 16754)	64 kPa
---------------------------------------	--------

XL TRACK UNDERCARRIAGE

GROUND PRESSURE - BLADE SU (ISO 16754)	61 kPa
--	--------

LGP TRACK UNDERCARRIAGE

GROUND PRESSURE - LGP BLADE (ISO 16754)	35 kPa
---	--------

BLADES

DOZERS

D6R2

Technical specifications

BLADE CAPACITY, S BLADE	4 m ³
-------------------------	------------------

SU BLADE CAPACITY	5.6 m ³
-------------------	--------------------

BLADE CAPACITY, A BLADE	4 m ³
-------------------------	------------------

SU XL BLADE CAPACITY	5.6 m ³
----------------------	--------------------

A XL BLADE CAPACITY	4 m ³
---------------------	------------------

LGP BLADE CAPACITY	3.8 m ³
--------------------	--------------------

BLADE WIDTH, S BLADE	3360 mm
----------------------	---------

SU BLADE WIDTH	3260 mm
----------------	---------

BLADE WIDTH, A BLADE	4166 mm
----------------------	---------

SU XL BLADE WIDTH	3260 mm
-------------------	---------

A XL BLADE WIDTH	4166 mm
------------------	---------

LGP BLADE WIDTH	4063 mm
-----------------	---------