



EXCAVATORS

326D2L

Tractafric
equipment



EXCAVATORS

326D2L

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

REFERENCE

BX06524

YEAR

2019

HOURS

1625

VIN

KER10920

AVAILABILITY

Sold

EXCAVATORS

326D2L

Technical specifications

ENGINE

NET POWER - ISO 9249 157.8 kW

ENGINE MODEL C7.1 Cat

ENGINE POWER - ISO 14396 159 kW

BORE 105 mm

STROKE 135 mm

DISPLACEMENT 7.01 l

HYDRAULIC SYSTEM

MAIN CIRCUIT: MAXIMUM FLOW 481 l/min (127 gal/min)

MAXIMUM PRESSURE: EQUIPMENT 35000 kPa

MAXIMUM PRESSURE - EQUIPMENT - LIFT MODE 38000 kPa

MAXIMUM PRESSURE: TRAVEL 35000 kPa

MAXIMUM PRESSURE: SWING 28400 kPa

SWING MECHANISM

SWING SPEED 9.8 RPM

MAXIMUM SWING TORQUE 106 kNm

WEIGHT

EXCAVATORS

326D2L

Technical specifications

OPERATING WEIGHT	25700 kg
------------------	----------

MAINTENANCE CAPACITIES

FUEL TANK CAPACITY	474 l
--------------------	-------

COOLING SYSTEM	25 l
----------------	------

ENGINE OIL	25 l
------------	------

SWING DRIVE	11.5 l
-------------	--------

FINAL DRIVE - EACH	4.5 l
--------------------	-------

HYDRAULIC SYSTEM - INCLUDING TANK	310 l
-----------------------------------	-------

HYDRAULIC TANK	147 l
----------------	-------

DIMENSIONS

BOOM	HD 5.9 m (19'4")
------	------------------

ARM	HD 2.95 m (9'8")
-----	------------------

BUCKET	HD 1.54 m ³ (2.01 yd ³)
--------	--

SHIPPING HEIGHT: CAB TOP	3000 mm
--------------------------	---------

HANDRAIL HEIGHT	3000 mm
-----------------	---------

SHIPPING LENGTH	10060 mm
-----------------	----------

REAR SWING RADIUS	3000 mm
-------------------	---------

EXCAVATORS

326D2L

Technical specifications

COUNTERWEIGHT GROUND CLEARANCE	1060 mm
--------------------------------	---------

GROUND CLEARANCE	440 mm
------------------	--------

TRACK LENGTH	4640 mm
--------------	---------

LENGTH TO CENTER OF ROLLERS	3830 mm
-----------------------------	---------

TRACK GAUGE	2590 mm
-------------	---------

TRANSPORT WIDTH	3190 mm
-----------------	---------

WORKING RANGES AND FORCES

MAXIMUM DIGGING DEPTH	6820 mm
-----------------------	---------

BOOM	HD 5.9 m (19'4")
------	------------------

ARM	HD 2.95 m (9'8")
-----	------------------

BUCKET	HD 1.54 m ³ (2.01 yd ³)
--------	--

MAXIMUM GROUND REACH	10120 mm
----------------------	----------

MAXIMUM CUTTING HEIGHT	9640 mm
------------------------	---------

MAXIMUM LOADING HEIGHT	6620 mm
------------------------	---------

MINIMUM LOADING HEIGHT	2390 mm
------------------------	---------

MAXIMUM DIGGING DEPTH FOR 2,440 MM (8 FT) FLA	6640 mm
---	---------

MAXIMUM VERTICAL WALL DIGGING DEPTH	5110 mm
-------------------------------------	---------

BUCKET DIGGING FORCE: ISO	166 kN
---------------------------	--------

EXCAVATORS

326D2L

Technical specifications

ARM DIGGING FORCE: ISO

121 kN