



EXCAVATORS

320-07GC

Tractafric
equipment



EXCAVATORS

320-07GC

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

REFERENCE

BX06508

YEAR

2021

HOURS

1868

VIN

DKJ30607

AVAILABILITY

Sold

EXCAVATORS

320-07GC

Technical specifications

ENGINE

NET POWER - ISO 9249 107 kW

ENGINE MODEL C4.4 Cat

ENGINE POWER - ISO 14396 108 kW

BORE 105 mm

STROKE 127 mm

DISPLACEMENT 4.4 l

HYDRAULIC SYSTEM

MAIN CIRCUIT: MAXIMUM FLOW 429 l/min (113 US gal/min)

MAXIMUM PRESSURE: EQUIPMENT 35000 kPa

MAXIMUM PRESSURE: TRAVEL 34300 kPa

MAXIMUM PRESSURE: SWING 25000 kPa

SWING MECHANISM

SWING SPEED 11.3 rpm

MAXIMUM SWING TORQUE 74.4 kNm

WEIGHT

OPERATING WEIGHT 20300 kg

EXCAVATORS

320-07GC

Technical specifications

MAINTENANCE CAPACITIES

FUEL TANK CAPACITY	345 l
--------------------	-------

COOLING SYSTEM	25 l
----------------	------

ENGINE OIL	15 l
------------	------

SWING REDUCTION GEAR: EACH	12 l
----------------------------	------

FINAL DRIVE - EACH	4 l
--------------------	-----

HYDRAULIC SYSTEM - INCLUDING TANK	234 l
-----------------------------------	-------

HYDRAULIC TANK	115 l
----------------	-------

DIMENSIONS

BOOM	Reach 5.7 m (18'8")
------	---------------------

ARM	Standard 2.9 m (9'6")
-----	-----------------------

BUCKET	1.0 m ³ (1.31 yd ³)
--------	--

SHIPPING HEIGHT: TOP OF CAB	2960 mm
-----------------------------	---------

HANDRAIL HEIGHT	2950 mm
-----------------	---------

SHIPPING LENGTH	9530 mm
-----------------	---------

TAIL SWING RADIUS	2830 mm
-------------------	---------

COUNTERWEIGHT GROUND CLEARANCE	1050 mm
--------------------------------	---------

GROUND CLEARANCE	470 mm
------------------	--------

EXCAVATORS

320-07GC

Technical specifications

TRACK LENGTH	4450 mm
--------------	---------

LENGTH TO CENTER OF ROLLERS	3650 mm
-----------------------------	---------

TRACK GAUGE	2380 mm
-------------	---------

TRANSPORT WIDTH	2980 mm
-----------------	---------

WORKING RANGES AND FORCES

MAXIMUM DIGGING DEPTH	6630 mm
-----------------------	---------

BOOM	Reach 5.7 m (18'8")
------	---------------------

ARM	Standard 2.9 m (9'6")
-----	-----------------------

BUCKET	1.0 m ³ (1.31 yd ³)
--------	--

MAXIMUM GROUND LEVEL REACH	9970 mm
----------------------------	---------

MAXIMUM CUTTING HEIGHT	9440 mm
------------------------	---------

MAXIMUM LOADING HEIGHT	6580 mm
------------------------	---------

MINIMUM LOADING HEIGHT	2260 mm
------------------------	---------

MAXIMUM VERTICAL WALL DIGGING DEPTH - 2440 N	6460 mm
--	---------

MAXIMUM DIGGING DEPTH - VERTICAL	6010 mm
----------------------------------	---------

BUCKET DIGGING FORCE - ISO	129 kN
----------------------------	--------

ARM DIGGING FORCE - ISO	99 kN
-------------------------	-------