



EXCAVATORS

330D2L

Tractafric
equipment



EXCAVATORS

330D2L

Overview

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

CAT® Certified Used

REFERENCE

BX06517

YEAR

2018

HOURS

4964

LOCATION

THAILAND

VIN

SZK11382

AVAILABILITY

Sold

EXCAVATORS

330D2L

Technical specifications

ENGINE

NET POWER - ISO 9249 157.8 kW

ENGINE MODEL C7.1 Cat

ENGINE POWER - ISO 14396 159 kW

BORE 105 mm

STROKE 135 mm

DISPLACEMENT 7.01 l

HYDRAULIC SYSTEM

MAIN SYSTEM: MAX FLOW 560 l/min (148 US gal/min)

MAXIMUM PRESSURE: IMPLEMENT 35000 kPa

MAXIMUM PRESSURE: TRAVEL 35000 kPa

MAXIMUM PRESSURE: SWING 28400 kPa

SWING MECHANISM

SWING SPEED 11.5 rpm

MAXIMUM SWING TORQUE 105 kNm

WEIGHT

OPERATING WEIGHT 28000 kg

EXCAVATORS

330D2L

Technical specifications

MAINTENANCE CAPACITIES

FUEL TANK CAPACITY	474 l
--------------------	-------

COOLING SYSTEM	25 l
----------------	------

ENGINE OIL	25 l
------------	------

SWING DRIVE (EACH)	10 l
--------------------	------

FINAL DRIVE (EACH)	5.5 l
--------------------	-------

HYDRAULIC SYSTEM (INCLUDING TANK)	310 l
-----------------------------------	-------

HYDRAULIC TANK	147 l
----------------	-------

DIMENSIONS

BOOM	Standard 6.15 m (20.2 ft)
------	---------------------------

ARM	Standard 3.2 m (10.5 ft)
-----	--------------------------

BUCKET	Extra Heavy Duty 1.60 m ³ (2.09 yd ³)
--------	--

SHIPPING HEIGHT: CAB TOP	3050 mm
--------------------------	---------

HANDRAIL HEIGHT	3050 mm
-----------------	---------

SHIPPING LENGTH	10420 mm
-----------------	----------

REAR END SWING RADIUS	3130 mm
-----------------------	---------

COUNTERWEIGHT CLEARANCE	1110 mm
-------------------------	---------

GROUND CLEARANCE	490 mm
------------------	--------

EXCAVATORS

330D2L

Technical specifications

TRACK LENGTH	4350 mm
--------------	---------

LENGTH TO CENTER OF ROLLERS	3490 mm
-----------------------------	---------

TRACK GAUGE	2390 mm
-------------	---------

TRANSPORT WIDTH	3190 mm
-----------------	---------

WORKING RANGES AND FORCES

MAXIMUM DIGGING DEPTH	7260 mm
-----------------------	---------

BOOM	Standard 6.15 m (20.2 ft)
------	---------------------------

ARM	Standard 3.2 m (10.5 ft)
-----	--------------------------

BUCKET	Extra Heavy Duty 1.60 m ³ (2.09 yd ³)
--------	--

MAXIMUM GROUND REACH	10690 mm
----------------------	----------

MAXIMUM CUTTING HEIGHT	9980 mm
------------------------	---------

MAXIMUM LOADING HEIGHT	6930 mm
------------------------	---------

MINIMUM LOADING HEIGHT	2280 mm
------------------------	---------

MAXIMUM FLAT BOTTOM CUT DEPTH OF 2,440 MM (7100 mm	
---	--

MAXIMUM VERTICAL WALL DIGGING DEPTH	5800 mm
-------------------------------------	---------

BUCKET DIGGING FORCE: ISO	179 kN
---------------------------	--------

ARM DIGGING FORCE: ISO	126 kN
------------------------	--------