



DOZERS

D6R2XL

Tractafric
equipment

CAT[®]

DOZERS

D6R2XL

Overview

Key information

BRAND

CAT®

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

CONDITION

CAT® Certified Used

YEAR

2019

HOURS

5500

LOCATION

Cameroon

VIN

TTT00638

AVAILABILITY

Available

DOZERS

D6R2XL

Technical specifications

ENGINE

ENGINE MODEL	C9 Cat
POWER - NET	148 kW
NOTE (1)	The announced net power is the power available at the flywheel wh...

D6R2 (TIER 2/STAGE II)

EMISSIONS	Chinese Stage II emissions standards for non-road engines, equivalent to EU Stage II
STANDARD - NET RATED POWER - ISO 9249/SAE J134 ¹	141 kW
STANDARD - NET RATED POWER - ISO 9249 (DIN)	192 mhp
XL/LGP - NET RATED POWER - ISO 9249/SAE J1349	158 kW
XL/LGP - NET RATED POWER - ISO 9249 (DIN)	215 mhp

D6R2 (TIER 3/STAGE III)

EMISSIONS	Chinese Stage III emissions standards for non-road engines, equivalent to EU Stage III
STANDARD - NET RATED POWER - ISO 9249/SAE J134 ¹	162 kW
STANDARD - NET RATED POWER - ISO 9249 (DIN)	220 mhp
XL/LGP - NET RATED POWER - ISO 9249/SAE J1349	176 kW
XL/LGP - NET RATED POWER - ISO 9249 (DIN)	239 mhp

MAINTENANCE CAPACITIES

Tractafric
equipment

CAT[®]

DOZERS

D6R2XL

Technical specifications

FUEL TANK 424 l

WEIGHT

OPERATING WEIGHT 18,984 kg

OPERATING WEIGHT - D6R2 (S) 18,984 kg

OPERATING WEIGHT - D6R2 (SU) 19,066 kg

OPERATING WEIGHT - D6R2 (A) 19,448 kg

OPERATING WEIGHT - D6R2 XL (SU) 19,914 kg

OPERATING WEIGHT - D6R2 XL (A) 19,969 kg

OPERATING WEIGHT - D6R2 LGP (S) 21,661 kg

STANDARD TRACK UNDERCARRIAGE

GROUND PRESSURE - BLADE A (ISO 16754) 64 kPa

XL TRACK UNDERCARRIAGE

GROUND PRESSURE - BLADE SU (ISO 16754) 61 kPa

LGP TRACK UNDERCARRIAGE

GROUND PRESSURE - LGP BLADE (ISO 16754) 35 kPa

BLADES

Tractafric
equipment

CAT[®]

DOZERS

D6R2XL

Technical specifications

BLADE CAPACITY, S BLADE	4 m ³
SU BLADE CAPACITY	5.6 m ³
BLADE CAPACITY, A BLADE	4 m ³
SU XL BLADE CAPACITY	5.6 m ³
A XL BLADE CAPACITY	4 m ³
LGP BLADE CAPACITY	3.8 m ³
BLADE WIDTH, S BLADE	3360 mm
SU BLADE WIDTH	3260 mm
BLADE WIDTH, A BLADE	4166 mm
SU XL BLADE WIDTH	3260 mm
A XL BLADE WIDTH	4166 mm
LGP BLADE WIDTH	4063 mm