



EXCAVATORS

336-08

Tractafric
equipment



EXCAVATORS

336-08

Overview

NEW MACHINE IN STOCK

Rops Cab A/C

Boom Reach 6.50m HD

Stick Reach 2.80m

DB Linkage Pin On

SD Bkt 2.12m3

Undercarriage 2740mm

Double Grouser Shoes 600mm

Bottom/Swivel/Track Motor Guards

6.8T Counterweight

8" Monitor w/ Rearview Camera

Working Lights

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

New

REFERENCE

BX06464

YEAR

2023

HOURS

810

LOCATION

VLISSINGEN, NL

VIN

MZR00206

AVAILABILITY

Available

EXCAVATORS

336-08

Technical specifications

ENGINE

ENGINE POWER - ISO9249 223 kW

ENGINE MODEL C7.1 Cat

BORE 105 mm

STROKE 135 mm

DISPLACEMENT 7.01 l

HYDRAULIC SYSTEM

MAIN HYDRAULIC CIRCUIT - MAX FLOW 560 l/min

MAXIMUM PRESSURE - EQUIPMENT 35000 kPa

MAXIMUM PRESSURE - EQUIPMENT - LIFT MODE 38000 kPa

MAXIMUM PRESSURE - TRAVEL 35000 kPa

MAXIMUM PRESSURE - SWING 29400 kPa

SWING MECHANISM

SWING SPEED 8.84 RPM

MAXIMUM SWING TORQUE 143 kNm

WEIGHT

OPERATING WEIGHT 35800 kg

EXCAVATORS

336-08

Technical specifications

MAINTENANCE CAPACITIES

FUEL TANK CAPACITY	600 l
--------------------	-------

COOLING SYSTEM	39 l
----------------	------

ENGINE OIL	25 l
------------	------

SWING DRIVE (EACH)	18 l
--------------------	------

FINAL DRIVE - EACH	8 l
--------------------	-----

HYDRAULIC SYSTEM (INCLUDING TANK)	373 l
-----------------------------------	-------

HYDRAULIC TANK	161 l
----------------	-------

DIMENSIONS

BOOM	Standard 6.5 m (21'4")
------	------------------------

ARM	Standard 3.2 m (10'6")
-----	------------------------

BUCKET	Standard 2.12 m ³ (2.77 yd ³)
--------	--

SHIPPING HEIGHT - CAB TOP	3180 mm
---------------------------	---------

HANDRAIL HEIGHT	3180 mm
-----------------	---------

SHIPPING LENGTH	11170 mm
-----------------	----------

REAR END SWING RADIUS	3530 mm
-----------------------	---------

COUNTERWEIGHT CLEARANCE	1260 mm
-------------------------	---------

GROUND CLEARANCE	510 mm
------------------	--------

EXCAVATORS

336-08

Technical specifications

TRACK LENGTH	5030 mm
--------------	---------

TRACK LENGTH TO CENTER OF ROLLERS	4040 mm
-----------------------------------	---------

TRACK GAUGE	2740 mm
-------------	---------

TRANSPORT WIDTH - 600 MM (24") SHOES	3340 mm
--------------------------------------	---------

WORKING RANGES AND FORCES

MAXIMUM DIGGING DEPTH	7560 mm
-----------------------	---------

BOOM	Standard 6.5 m (21'4")
------	------------------------

ARM	Standard 3.2 m (10'6")
-----	------------------------

BUCKET	Standard 2.12 m ³ (2.77 yd ³)
--------	--

MAXIMUM GROUND REACH	11110 mm
----------------------	----------

MAXIMUM CUTTING HEIGHT	10340 mm
------------------------	----------

MAXIMUM LOADING HEIGHT	7040 mm
------------------------	---------

MINIMUM LOADING HEIGHT	2540 mm
------------------------	---------

MAXIMUM FLAT BOTTOM CUTTING DEPTH OF 2440 l 7410 mm	
---	--

MAXIMUM VERTICAL WALL DIGGING DEPTH	5860 mm
-------------------------------------	---------

BUCKET DIGGING FORCE - ISO	209 kN
----------------------------	--------

ARM DIGGING FORCE - ISO	166 kN
-------------------------	--------