



EXCAVATORS

340-08

Tractafric
equipment



EXCAVATORS

340-08

Overview

NEW MACHINE

Rops Cab A/C

Boom Reach 6.50m HD+

Stick Reach 3.20m HD+

DB Linkage Pin On

SD Bkt 2.38m3

Undercarriage 2,740mm

Double Grouser Shoes 600mm

Bottom/Swivel/Track Motor Guards

7.5T Counterweight

8" Monitor w/ Rearview Camera

Working Lights

Contact and information

BY EMAIL

frederique.simmons@tractafric.com

david.guerrey@tractafric.com

BY PHONE

+212 522 438 222

+33 1 71 90 40 50

Key information

BRAND

CAT®

CONDITION

New

REFERENCE

BX06465

YEAR

2023

HOURS

35

LOCATION

VLISSINGEN, NL

VIN

WFK00112

AVAILABILITY

Sold

EXCAVATORS

340-08

Technical specifications

ENGINE

ENGINE POWER - ISO 9249 258 kW

ENGINE MODEL C9.3B Cat

BORE 115 mm

STROKE 149 mm

DISPLACEMENT 9.3 l

HYDRAULIC SYSTEM

MAIN HYDRAULIC CIRCUIT: MAX FLOW 560 l/min

MAXIMUM PRESSURE: EQUIPMENT 35,000 kPa

MAXIMUM PRESSURE - EQUIPMENT - LIFT MODE 38,000 kPa

MAXIMUM PRESSURE: TRAVEL 35,000 kPa

MAXIMUM PRESSURE: SWING 29,400 kPa

SWING MECHANISM

SWING SPEED 8.84 rpm

MAXIMUM SWING TORQUE 143 kNm

WEIGHT

OPERATING WEIGHT 37,100 kg

EXCAVATORS

340-08

Technical specifications

MAINTENANCE CAPACITIES

FUEL TANK CAPACITY	600 l
--------------------	-------

COOLING SYSTEM	40 l
----------------	------

ENGINE OIL	32 l
------------	------

SWING DRIVE (EACH)	18 l
--------------------	------

FINAL DRIVE (EACH)	8 l
--------------------	-----

HYDRAULIC SYSTEM - INCLUDING TANK	373 l
-----------------------------------	-------

HYDRAULIC TANK	161 l
----------------	-------

DIMENSIONS

BOOM	Standard 6.5 m (21'4")
------	------------------------

ARM	Standard 3.2 m (10'6")
-----	------------------------

BUCKET	HD 2.36 m ³ (3.08 yd ³)
--------	--

SHIPPING HEIGHT: CAB TOP	3180 mm
--------------------------	---------

HANDRAIL HEIGHT	3180 mm
-----------------	---------

SHIPPING LENGTH	11180 mm
-----------------	----------

REAR END SWING RADIUS	3530 mm
-----------------------	---------

COUNTERWEIGHT GROUND CLEARANCE	1260 mm
--------------------------------	---------

GROUND CLEARANCE	510 mm
------------------	--------

EXCAVATORS

340-08

Technical specifications

TRACK LENGTH	5030 mm
--------------	---------

TRACK LENGTH TO CENTER OF ROLLERS	4040 mm
-----------------------------------	---------

TRACK GAUGE	2740 mm
-------------	---------

TRANSPORT WIDTH: 600 MM (24") SHOES	3340 mm
-------------------------------------	---------

WORKING RANGES AND FORCES

MAXIMUM DIGGING DEPTH	7510 mm
-----------------------	---------

BOOM	Standard 6.5 m (21'4")
------	------------------------

ARM	Standard 3.2 m (10'6")
-----	------------------------

BUCKET	HD 2.36 m³ (3.08 yd³)
--------	-----------------------

MAXIMUM GROUND REACH	11060 mm
----------------------	----------

MAXIMUM CUTTING HEIGHT	10320 mm
------------------------	----------

MAXIMUM LOADING HEIGHT	7080 mm
------------------------	---------

MAXIMUM FLAT BOTTOM CUT DEPTH OF 2440 MM (± 7360 mm	
---	--

MAXIMUM VERTICAL WALL DIGGING DEPTH	5620 mm
-------------------------------------	---------

BUCKET DIGGING FORCE: ISO	210 kN
---------------------------	--------

ARM DIGGING FORCE: ISO	166 kN
------------------------	--------